



Taylor & Jones Ltd
reamer specialists

Crosland Road Industrial Estate,
Netherton,
Huddersfield
HD4 7DQ

Tel: +44 (0) 1484 665321
Fax: +44 (0) 1484 666952
E-mail: reamers@taylorandjones.co.uk
www.taylorandjones.co.uk

Adjustable Floating Reamers

Verstellbare Pendelreibahlen

Alésoirs Flottant

A·F Reamers

HSS Blades SL Type for Blind Holes

RANGE 3/4" to 4"

19.0mm to 101.6mm

LIST CODE FRS0HLR

SPARES AVAILABLE



Code	Symbol	Range d1		L1	L2	Blade Length	Morse Taper No.	Blade Set Code
		Inch	mm					
FRS01HLR	SL1	3/4-13/16	19.0-20.6	60.8	125.8	14.0	1	FRS01HLB
FRS02HLR	SL2	13/16-7/8	20.6-22.2	60.8	125.8	14.0	1	FRS02HLB
FRS03HLR	SL3	7/8-15/16	22.2-23.8	65.7	130.8	15.2	1	FRS03HLB
FRS04HLR	SL4	15/16-1	23.8-25.4	65.7	130.8	15.2	1	FRS04HLB
FRS05HLR	SL5	1-1.1/8	25.4-28.6	78.5	156.3	17.9	2	FRS05HLB
FRS06HLR	SL6	1.1/8-1.1/4	28.6-31.8	79.0	157.6	18.4	2	FRS06HLB
FRS07HLR	SL7	1.1/4-1.3/8	31.8-34.9	88.5	167.1	20.3	2	FRS07HLB
FRS08HLR	SL8	1.3/8-1.1/2	34.9-38.1	89.4	168.8	21.2	2	FRS08HLB
FRS09HLR	SL9	1.1/2-1.3/4	38.1-44.4	105.6	204.0	25.4	3	FRS09HLB
FRS10HLR	SL10	1.3/4-2	44.4-50.8	109.1	207.5	28.1	3	FRS10HLB
FRS11HLR	SL11	2-2.3/8	50.8-60.3	119.7	243.5	33.7	4	FRS11HLB
FRS12HLR	SL12	2.3/8-2.3/4	60.3-69.8	121.3	245.1	33.7	4	FRS12HLB
FRS13HLR	SL13	2.3/4-3.1/4	69.8-82.5	134.1	257.9	38.9	4	FRS13HLB
FRS14HLR	SL14	3.1/4-4	82.5-101.6	158.2	283.6	45.5	4	FRS14HLB

A·F Reamers

TCT Blades SL Type for Blind Holes

RANGE 3/4" to 4"

19.0mm to 101.6mm

LIST CODE FRS0CLR

Code	Symbol	Range d1		L1	L2	Blade Length	Morse Taper No.	Blade Set Code
		Inch	mm					
FRS01CLR	SL1	3/4-13/16	19.0-20.6	60.8	125.8	14.0	1	FRS01CLB
FRS02CLR	SL2	13/16-7/8	20.6-22.2	60.8	125.8	14.0	1	FRS02CLB
FRS03CLR	SL3	7/8-15/16	22.2-23.8	65.7	130.8	15.2	1	FRS03CLB
FRS04CLR	SL4	15/16-1	23.8-25.4	65.7	130.8	15.2	1	FRS04CLB
FRS05CLR	SL5	1-1.1/8	25.4-28.6	78.5	156.3	17.9	2	FRS05CLB
FRS06CLR	SL6	1.1/8-1.1/4	28.6-31.8	79.0	157.6	18.4	2	FRS06CLB
FRS07CLR	SL7	1.1/4-1.3/8	31.8-34.9	88.5	167.1	20.3	2	FRS07CLB
FRS08CLR	SL8	1.3/8-1.1/2	34.9-38.1	89.4	168.8	21.2	2	FRS08CLB
FRS09CLR	SL9	1.1/2-1.3/4	38.1-44.4	105.6	204.0	25.4	3	FRS09CLB
FRS10CLR	SL10	1.3/4-2	44.4-50.8	109.1	207.5	28.1	3	FRS10CLB
FRS11CLR	SL11	2-2.3/8	50.8-60.3	119.7	243.5	33.7	4	FRS11CLB
FRS12CLR	SL12	2.3/8-2.3/4	60.3-69.8	121.3	245.1	33.7	4	FRS12CLB
FRS13CLR	SL13	2.3/4-3.1/4	69.8-82.5	134.1	257.9	38.9	4	FRS13CLB
FRS14CLR	SL14	3.1/4-4	82.5-101.6	158.2	283.6	45.5	4	FRS14CLB

